


NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

Test Device Prevents Weld Joint Damage by Eliminating Axial Pin Forces on Unpotted Modules



The problem:

To design a device for testing unpotted electronic modules that will prevent weld joint damage by eliminating axial or displacing forces on connector pins.

The solution:

A test device designed to make electrical connection to pins on unpotted modules which do not introduce any displacing forces of the pins. The pins are spaced in a potting header, but are free to slide in and out except for restraint from welded wire joints. The de-

vice consists of a box frame, a carriage with gold plated phosphor bronze contact springs, a module positioning reaction plate, carriage drive, stops, wiring, and miscellaneous hardware.

How it's done:

The carriage holds the contact springs in a matrix identical to the module pin matrix and the positioning plate matrix. With the carriage in the retracted position, the springs are completely clear of the positioning plate holes. The holes are slightly larger than the

(continued overleaf)

unpotted module pins and thus the pins may enter without force.

Advancing the carriage with the drive screw (approximately 0.05 inch) brings the springs into contact with the pins immediately below the positioning plate (approximately 0.1 inch) which prevents the module pins from moving away. A mechanical stop prevents carriage overtravel and allows a controlled spring pressure on the module pins.

Notes:

1. The contact springs are wired to standard connectors for the interface with test equipment.
2. The position of the contact springs allows testing of unpotted modules with pins extending only 0.25 inch or modules with pins up to 1.0 inch.

3. Inquiries concerning this innovation may be directed to:

Technology Utilization Officer
Lewis Research Center
21000 Brookpark Road
Cleveland, Ohio 44135
Reference: B67-10359

or

New Technology Representative
General Dynamics/Convair Division
Mail Zone 103-19
5001 Kearny Villa Road
San Diego, California 92112
Reference: B67-10359

Patent status:

No patent action is contemplated by NASA.

Source: R. E. Cree
of General Dynamics/Convair
under contract to
Lewis Research Center
(LEW-10201)

KSC HQS.

1
RM. 1427
IS-SAF